

TELEINDUSTRIA srl

phone: +39 02 45 71 37 29

email: sales@teleindustria.it

website: **www.teleindustria.com**

Industrial VoIP IP66 Intercom Station with robust IK10 aluminum enclosure with keypad and loudspeaker **OCEAN-ip™ model OCSip497M1**

OCEAN-ip™ WALL MOUNTED SLAVE STATION



Professional **IP66 & IK10** Heavy-Duty **OCEAN™** intercom station, **aluminum** body and **aluminum heavy duty Call Button**, hands-free and/or PTT conversation, suitable for high noise areas (up to 90dB), with integrated microphone and integrated 5W loudspeaker.

- Single Button to call the Master Station
- Hands-Free or Push-to-Talk conversation mode driven by the Master Station, for high quality conversations in high noisy areas (>90dB)

ORDER CODES

OCSip497M1: 1 button

Push button activatable with a 20 Joule pressure in all directions (thus also usable by people with reduced mobility), accordingly to most severe rules.

OCEAN-ip™ SERVER-LESS

OCEAN-ip™ is a **professional industrial intercom system** ready to work on ETHERNET, with no needs of any Server.

However, the intercom stations **OCEAN-ip™** can also be connected to any SIP server and of course to the **TELEINDUSTRIA DESQO™** professional platform.

Main Characteristics

Protocols: VoIP SIP & P2P
integrated loudspeaker: 5 W_{RMS} 90 dB@1m
built-in microphone: electret
Power-supply: PoE or 12Vdc±10%
optional power-supply (on demand): 24-48Vdc ±10%

OCEAN-ip is a professional industrial intercom system ready to work on ETHERNET, with **no needs of any Server**. However, the intercom stations **OCEAN-ip** can also be connected to any SIP server and of course to the **TELEINDUSTRIA DESQO™** professional platform.

Shock-Resistance: IK10 [EN 60950]
Protection index: IP66 [EM 60529]
Working temperature: -40 °C ÷ +70°C
Body: 100% aluminum
Mounting: wall-mounting
Wiring: screw terminals Ø1,5mm
Dimensions: 160 x 300 x 67 mm
Weight: 3,4 kg
Cables inlets: 2 holes Ø20mm, cables Ø5÷8mm
MTBF: 180.000 hours
MTTR: <3 minutes

