

TELEINDUSTRIA srl

Phone: (39) 2 4571 3729

E-mail: sales@teleindustria.it

Web-site: **www.teleindustria.com**

VoIP telephone call repeater IP66 aluminum enclosure 120dB@1m, visible @360° model SAL425-ip

PHONEALERT-ip™



Protection rating: IP66
Impact resistance: IK8
Operating temperature: -40°C to +70°C
Construction material: Aluminum
Color: Orange RAL2003
Optical diffuser color: colors available on request
Installation: Wall-mounted
Dimensions: 217 x 253 x 132 mm
Weight: 2.1 kg

Order Codes

SAL425-ip-230-W: IP drive - 230Vac – White lens

Add the letter W-Y-O-R-B-G to select the lens color.

PHONEALERT™ SAL425-ip is a robust optical and acoustic VoIP telephone call repeater, ready to work in association with any **iPBX – SIP VoIP servers**.

It must be **registered on an iPBX as a standard VoIP telephone**, so that it is activated whenever a call is sent to a specific phone or to a specific group of phones.

It is designed for use in industrial environments with high ambient noise. It is contained in a sturdy aluminum enclosure, with **IP66** and **IK10** protection rating, suitable for wall installation.

CONNECTION

ETHERNET: RG45 cat.6 – max 90m
Power-supply: 230Vac

OPTICAL SECTION

Equipped with an industrial tropicalized electronic circuit (working conditions -40°C +70°C – 98% humidity) driving a 4 LED strips.

LED Flash: 380 lumens (white lens)
Consumption: max 55W

Normally delivered with WHITE lens, it can be delivered on demand with ORANGE, RED, GREEN or BLUE lens.

ACOUSTIC SECTION

SPL @ 1 m: 120dB

The output level is adjustable via an internal potentiometer accessible during installation. Up to 8 programmable melodies are available through DIP switches.

