

TELEINDUSTRIA srl

 Phone:(39) 2 45713729
 Fax:(39) 2 45714000
 E-mail: sales@teleindustria.it
 Web-site: www.teleindustria.com

Weather-proof IP66 analogue SMART industrial telephone, shock-proof IK10 with auto fault-detection & audio test model TEL457T / TEL457TV


AVAILABLE COLORS

YELLOW RAL1023	GREY RAL7030	BLACK RAL9005	RED RAL3020	ORANGE RAL2003

MTBF: >180.000 hours
 MTTR: 3 minutes
 IP-rating: IP66 [EN 60529]
 Impacts resistance: IK10 [EN 60068]
 Max relative humidity: 98% [EN 60068]
 Operating temperatures: -40°C ÷ +70°C
 Handset's cord: stainless steel INOX, resistance 200kg
 Dimensions: 190x240x117 mm
 Weight: 3,6 kg
 Cables entrances: 2 holes M20 (1 cablegland + 1 plug)

HARDYPHONE® is a **SMART** analogue industrial telephone, with a very strong body made of aluminum (thickness 5mm) vandal resistant and shock proof **IK10**, weather-proof **IP66**. Designed for **20 years life** in heavy industrial areas. An unusual feature of the **HARDYPHONE®** series is the **handset entirely made of aluminum**, with a stainless steel cord capable of supporting a **pulling force of over 200kg**. Even the keyboard, with **single aluminum keys**, offers characteristics of high strength and impact resistance.

MAIN CHARACTERISTICS

Powered by telephone line: 12÷60 Vdc
 Ringing voltage: 25÷100 V_{EFF}
 Dialling: DTMF
 Electronic Bell: up to 95dB@1m, adjustable
 Hook: magnetic, high protection
 Programmable: 100% programmable remotely by DTMF

EXTENDED KEYPAD

15 keys keypad, with single aluminum buttons, with double function activated by the button Fn:

- 12 buttons (*, #, 0, 1...9)
- R (flash), RP (last number redial)
- Pre-memorized call buttons (M1÷M8)
- Volume adjustment V+, V-
- Hook key (hands-free mode on TEL457TV)
- Door opening button, on DTMF password
- Red LED indicating "on line" or "incoming call"
- Blue LED indicating good state of service
- Noise cancelling circuit

OPTIONAL FUNCTIONS

- External Head-set jack
- Local audio test and Fault-Detection
- Hands-Free Full-Duplex (TEL457TV only)
- Booster amplifier for external loudspeaker (supplied@12Vcc)
- Auxiliary hook contact
- Jack for external headset with microphone
- Call repeating relay for external repeaters
- Remote command relay on password DTMF
- Remote diagnostic software TelDia®
- Fault Alarm Relay FAR-01 (needs +12/24Vdc)

AFD - Automatic Fault-detection

AFD is the function of **automatic periodical test** of all the functions and main devices of the telephone, including **audio test of microphone and earpiece**. The state of service is indicated by the **flashing blue LED**. A Fault-Relay module (model FAR-01) is available on demand.

MISSING/FAULTY HANDSET

The hands-free version (TEL457TV) still operates also when the handset is missing or out of service.

ORDER CODES

TEL457T 15 double function keys
 TEL457TV 15 double function keys + Hands-Free
 TEL457M0 Without keypad
 Option JK Jack for headset
 Option R Internal Relay for external repeaters