

TELEINDUSTRIA srl

phone: +39 02 45713729

email: sales@teleindustria.it

website: **www.teleindustria.com**

Smart VoIP Hands-Free telephone watertight IP66 & shockproof IK10 wall mounting, Remote Interrogation Automatic Fault Detection model TEL249M1P-Sip

STEELVOX-ip™



STEELVOX-ip™ is a **SMART VoIP (SIP)** Full-Duplex hands-free telephone, made with a strong INOX body (thickness 2mm) vandal-resistant and resistant to shocks **IK10**, with **IP66** protection. The family **STEELVOX-ip™** is suitable to be installed in any pillar in our range. It ensures a **high quality of conversation** in industrial environments with **high ambient noise**.

STEELVOX-ip™ is vastly used both to carry out functions of **Service & SOS Emergency**.

TEL249M1-VoIP with 1 Call Button

The **TEL249M1-Sip** is equipped with only one **red button Ø20mm** for the automatic dialling of one or more **pre-stored telephone numbers**. If properly programmed, the button can be used for manual answer to incoming calls. However, you can program your phone to automatically answer after a predetermined number of ring tones.

- Red LED indicating "on line" status
- Blue LED signalling good work conditions or fault

MAIN FEATURES

Protocol: SIP
Codec: G711 ITU-T
Power: PoE (IEEE 802.3af)
SIP Servers: up to 3 SIP servers
Electronic Bell: up to 95dB@1m, adjustable
Programmable: webpage

OPTIONS

- Remote diagnostic interrogation by TelDia™
- Programmable Relay activated on events (On/Off contact free of voltage)

AFD - Automatic Fault-Detection

The telephone is equipped with the AFD (Automatic Fault Detection) function, so that all the parameters of the telephone are periodically tested, including the audio-test of microphone and loudspeaker. A Blue LED is flashing to show that the telephone is in good working conditions. The status of the telephone can be remotely interrogated by the software TelDia™.

APPLICABLE RULES

EN 50121-4; EN 60529; EN 60068; EN 62368-1; EN 62262;

ORDER CODES

TEL249M1-Sip 1 button Ø20mm

STEELVOX™ FAMILY

STEELVOX™ is available with 1, 2, 4, 8 buttons for pre-memorized numbers or with full telephone keypad.



Protection index : IP66 [EN 60529]
Impact Resistance : IK10 [EN 60068]
Max relative humidity: 98%
Operating temperatures: -40°C ÷ +70°C
Material: INOX AISI316 marine degree
MTBF: >180.000 hours
MTTR: 3 minutes
Dimensions: 180x260x58 mm
Weight: 3,0 kg