

TELEINDUSTRIA srl

Phone:(39) 2 45713729

E-mail: sales@teleindustria.it

Web-site: www.teleindustria.com

VoIP telephone for Clean Rooms WASHABLE & DECONTAMINABLE Hands-Free, suitable for noisy areas model TEL251TD-Sip

CLEANVOX-ip™



CLEANVOX-ip™ TEL251TD is designed to be easily installed in most of the structures used in clean rooms. A stainless-steel frame for wall surface mounting is also available.

CLEANVOX-ip™ TEL251TD is suitable for mounting in cleanrooms classified according to ISO 14644-1, BS 5295, US FED STD 209E standards.

Complies with the most stringent standards for electromagnetic compatibility:

EN55011:2007+A2:2007; EN55022:2006 +A1:2007;
EN55024:1998+A1:2001+A2:2003; EN61000-6-2:2005; EN61000-6-4:2007

Protection index [IEC 60529]IP66-IP67
Body material:stainless-steel INOX + microban®
Operating temperatures: -20°C +70°C
Mounting: flush-mounting
Termination:screw terminals
Weight: 2,0 kg
Dimensions: 125 x 280 x 33 mm (front plate 2mm)
Wiring: RJ45
Dimensions: 125 x 280 x 33 mm (front plate 2mm)

CLEANVOX-ip™ TEL251TD-Sip is an IP66 watertight **WASHABLE** and **DECONTAMINABLE VoIP (SIP)** telephone designed for use in sterile rooms. Made with front in **AUTOTEX®AM** with **MICROBAN®** antimicrobial protection, free of holes and roughness, easily decontaminated by washing with detergents and bactericidal preparations.

It is designed for flush-mounting. It guarantees excellent **full-duplex hands-free** operation, even in **areas with high ambient noise**.

Hands Free Full-Duplex and Push-to-Talk

Equipped with the **XCS-182 native VoIP phone card**, **CLEANVOX-ip™** ensures high quality **Full-Duplex conversation** in environments with high ambient noise. However, to guarantee a conversation of excellent quality even in **highly noisy places (>90dB)**, it is possible to switch to **Push-to-Talk mode** using the PTT key, which also includes two Tx/Rx LEDs which indicate the transmission and reception status.

MAIN FEATURES

Dotato della scheda VoIP nativa XCS-182 release 2022-1, HDVoice, DESQO™ ready.

Protocol: SIP
Power source: PoE or 12Vdc
SIP Servers: up to 3 Server SIP
Bell: up to 90dB@1m
Programming: via webpage
Standard Keypad: 0÷9 * # R RP
Memory keys: Memory 1 & 2
Volume: volume +/-
Secure Key: for door opening on password
PTT button with Rx/Tx LEDs: Push-to-talk function
MTBF: > 180.000 hours
MTTR: 3 minutes

Server SIP and/or Peer-to-Peer

CLEANVOX-ip™ is compatible with any VoIP SIP server, naturally including the **TELEINDUSTRIA DESQO™** server. It is also **possible to operate in Peer to Peer** mode without the need for any Server.

AFD Automatic Fault Detection

Periodic automatic check of all elements, including loudspeaker and microphone audio test. Good working status is indicated by a symbol on the display, which changes in the event of a general failure or lethal failure.

OPTIONS

An optional alarm relay can be activated in the event of a fault.

ORDER CODES

TEL251TD-Sip full keypad + display