

TELEINDUSTRIA srl

Phone:(39) 2 45713729

E-mail: sales@teleindustria.it

Web-site: **www.teleindustria.com**

Weather-proof IP66 analogue rugged transportable telephone for maintenance and survey teams model TLP401M1

SERVOPHONE®



Body material / Color: Polyester/Orange
Handset: IP66 aluminum black painted
Mounting: portable
Termination: extensible cord with plug
Dimensions: 305 x 270 x 144 mm
Weight: 4,6 kg
IP-rating: IP67 (door closed) & IP66
Shocks resistance: IK10
MTBF: 180.000 hours
MTTR: 3 min

SERVOPHONE® is available also in 2 lines versions
TEL402M1T: one hot-line CB section and one ACB section with full keypad. The family SERVOPHONE® can be easily personalized on the base of the needs of customers. Refer to our commercial service for more information.



SERVOPHONE® is used by maintenance and emergency teams, typically on railways, tunnels, oil & gas streams. Exceptionally robust, it can be used outdoor in all weather conditions.

The **transportable enclosure** is made of polyester while the internal partes are made of aluminum. The enclosure is **protected IP67** when door is closed. The handset, accessible when door is open, is made of aluminum and it is protected IP66. Handset is equipped with a strong coiled cord, extensible to 1,5 meters.

One RED aluminum button allows to reply to incoming calls, and it can be used for the **automatic dialling of emergency numbers**. Of course **TEL401** can work in **Hot-Line mode** accordingly to the programmed function on the PBX.

Electrical Characteristics:

Powered by telephone line: 12÷60 Vdc
Ringing voltage: 25÷100 Veff
Dialling: DTMF
Electronic Bell: up to 85dB@1m, adjustable
Hook: magnetic, high protection
Programmable: 100% programmabile remotely by DTMF
MTBF: > 180.000 hours
MTTR: 3 minutes

Operating functions:

Keypad: 1 auto-dialling button
Conversation: Handset Full-Duplex mode
Red LED: indicating "on line" or "incoming call"
Blue LED: indicating fault conditions
Programming: 100% by DTMF
Remote diagnostic: software TelDia®

Audio Test & Local Diagnostic

The intelligent electronic card XCS-91-30 is equipped with the Audio Local Test function to make the periodical analyze of microphone and earpiece. Some other parameters are periodically tested and memorized to be available at a remote interrogation by the software TelDia®.

CODES COMMANDE

TEL401M1..... Analog SMART – 1 button
TEL401M2..... Analog SMART – 2 buttons

