

TELEINDUSTRIA srl

Phone:(39) 2 45713729

Fax:(39) 2 45714000

E-mail: sales@teleindustria.it

Web-site: www.teleindustria.com

Weather-proof IP66 analogue rugged transportable telephone for maintenance and survey teams model TLP402M1T

SERVOPHONE®



SERVOPHONE® is used by maintenance and emergency teams, typically on railways, tunnels, oil & gas streams. Exceptionally robust, it can be used outdoor in all weather conditions. The transportable **enclosure with door is made of polyester** and the internal parts are made of aluminum. The handset is made of aluminum, **weather-proof IP66**, and it is equipped with a **strong coiled cord**.

TLP402M1T is equipped to work on two separate analog lines, the first in traditional **ACB mode with full keypad** and the second works in **CB Hot-Line** (autodialling) mode.

Electrical Characteristics:

Powered by telephone line: 12÷60 Vdc
 Ringing voltage: 25÷100 VEFF
 Dialling: DTMF
 Electronic Bell: up to 85dB@1m, adjustable
 Hook: magnetic, high protection
 Programmable: 100% programmabile remotely by DTMF
 MTBF: > 180.000 hors
 MTTR: 3 minutes

Operating functions:

Keypad: 1 auto-dialling button
 Conversation: Handset Full-Duplex mode
 Red LED: indicating "on line" or "incoming call"
 Blue LED: indicating fault conditions
 Programming: 100% by DTMF
 Remote diagnostic: software TelDia®

Audio Test & Local Diagnostic

The intelligent electronic card XCS-91-30 is equipped with the Audio Local Test function to make the periodical analyze of microphone and earpiece. Some other parameters are periodically tested and memorized to be available at a remote interrogatiron by the software TelDia®.

CODES COMMANDE

TLP402M1T..... CB + ACB (2 lines)
 TLP401M1..... CB (1 line)



Body material / Color: Polyester/Orange
 Handset: IP66 aluminum black painted
 Mounting: portable
 Termination: extensible cord with plug
 Dimensions: 304 x 360 x 194 mm
 Weight: 6,7 kg
 IP-rating: 66 (with door open or closed)
 Shocks resistance: IK10
 MTBF: 180.000 hours
 MTTR: 3 min

