

TELEINDUSTRIA srl

phone: ..... +39 02 45713729

email: ..... sales@teleindustria.it

website: ..... **www.teleindustria.com**

## Smart VoIP (SIP) Hands-Free telephone watertight IP66 & shockproof IK10, Automatic Fault Detection & Remote Interrogation, model TEL487M8-Sip

### HARDYVOX-ip™



**HARDYVOX-ip™** is a **SMART VoIP (SIP)** Full-Duplex hands-free telephone, made with a strong aluminum body (thickness 5mm) **vandal-resistant** and resistant to shocks **IK10**, with **IP66** protection.

The family **HARDYVOX-ip™** is suitable to be installed on walls or pillars. It ensures a **high quality of conversation** in industrial and public environments with **high ambient noise**.

**HARDYVOX-ip™** is vastly used both to carry out functions of **Service & SOS Emergency**.

The model **TEL487M8-Sip** is equipped with two buttons for calling pre-stored numbers. The **HARDYVOX-ip™** range includes numerous variants, including a version with extended metallic telephone 15 buttons keypad.

#### TEL487M8 with 8 Call Buttons

The **TEL487M8** is equipped with **8 buttons** for the automatic dialling of one or more **pre-stored telephone numbers**. If properly programmed, the buttons can be used for manual answer to incoming calls. However, you can program your phone to automatically answer after a predetermined number of ring tones.

- Red LED indicating "on line" status
- Blue LED signalling good work conditions or fault

#### Electrical Characteristics

Equipped with the native VoIP electronic card XCS-182 release 2022-1, HD Voice, DESQO™ ready.

Protocol: ..... SIP

Power: ..... PoE or 12Vdc

SIP Servers: ..... up to 3 SIP servers

Electronic Bell: ..... up to 95dB@1m, adjustable

Hook: ..... magnetic, high protection

Programmable: ..... webpage

#### Additional functions (options)

- Auto Fault detection with audio local test
- Auxiliary hook contact
- Fault alarm relay
- 0dB audio output
- Remote diagnostic interrogation by TelDia®

#### Automatic Fault-Detection function:

The telephone can be equipped with the optional function of "**fault detection**", so that all the parameters of the telephone are periodically tested, including the audio-test of microphone and loudspeaker. A **Blue LED** is flashing to show that the telephone is in good working conditions. The status of the telephone can be remotely interrogated by the specialized **software TelDia®**.

#### ORDER CODES

TEL487M1-Sip ..... 1 button  
TEL487M2-Sip ..... 2 buttons  
TEL487M4-Sip ..... 4 buttons  
TEL487M8-Sip ..... 8 buttons  
TEL487T-Sip ..... full telephone keypad



#### AVAILABLE COLORS

YELLOW RAL1023	YELLOW RAL1023	YELLOW RAL1023	YELLOW RAL1023	YELLOW RAL1023

Protection index: ..... IP66 [EN 60529]  
Shock resistance: ..... IK10 [EN 60068]  
Mx. Relative Humidity [EN 60068-2-30] ..... 98%  
Operating temperatures: ..... -40°C ÷ +70°C  
Material: ..... aluminum  
MTBF: ..... >180.000 hours  
MTTR : ..... 3 minutes  
Dimensions : ..... 300 x 160 x 67 mm  
Weight: ..... 3,6 kg  
Cables entrance: ..... 2 holes Ø20mm with cablegland