

TELEINDUSTRIA srl

Phone:(39) 2 45713729

Fax:(39) 2 45714000

E-mail: sales@teleindustria.it

Web-site:..... www.teleindustria.com

Industrial SMART VoIP Telephone weather-proof IP66 & IK10 for marine & railways applications fault-detection & remote monitoring model TEL605T-VoIP

NAVYPHONE-ip®



Protection index: IP66 [EN 60529]
Shock-Resistance: IK08 [EN 60068]
Working temperature: -40°C +70°C
Body: GRP (Glass Reinforced Polyester)
Handset's cord: robust coiled cord for heavy duty
Mounting: on wall
Dimensions: 370 x 270 x 190 mm
Weight: 4,6kg
Cables inlets: 2 holes Ø20mm,
MTBF: 250.000 hours
MTTR: <3 minutes

AVAILABLE COLORS

YELLOW	GREY	BLACK	RED	ORANGE
RAL1023	RAL7030	RAL9005	RAL3020	RAL2003



NAVYPHONE® TEL605T-VoIP is a **SMART** industrial VoIP SIP telephone, **watertight IP66** and **impacts resistant IK10**, with 15 keys keypad + Function key (Fn). Designed for the **marine environment** (totally protected against corrosion) and **Railways**. **NAVYPHONE®** are designed for a **life of >20 years** in harsh environments.

It is equipped with a **strong door** with an handle, in order to **keep clean the handset** and to support symbols on the front. The protection index IP66 is guaranteed with open door, yet.

Main Characteristics:

Powered: 12Vdc or PoE
Hook: magnetic, high protection

Ringing Bell

TEL605T/VoIP: 65dB@1m (door closed)
95dB@1m (door open)

TEL605T-SE/VoIP: 95dB (doore open/clsoed)

Extended Keypad:

15 keys keypad, double function activated by the button Fn:

- 12 buttons (*, #, 0,1...9)
- R (flash), RP (last number redial)
- Pre-memorized call buttons (M1÷M8)
- Volume adjustment V+, V-
- Hook key
- Red LED indicating "on line" or "incoming call"

Optional functions:

- External Head-set jack
- Local audio test and Fault-Detetction
- Blue LED for indication of Fault condition
- Booster amplifier for external loudspeaker (supplied@12Vcc)
- Auxiliary hook contact
- Call repeating relay for external repeaters
- Remote command relay on password DTMF
- Remote diagnostic software TelDia®

Automatic Fault-detection

Automatic periodical test of all the functions and main devices of the telephone, including audio test of microphone and earpiece. The state of service is indicated by the flashing blue LED. A Fault-Relay module is available on demand.



ORDER CODES

TEL605T-HS50X-ip:INOX cord
TEL605T-HS50S-ip coiled cord
TEL605T-SE-HS50X-ip: INOX cord – Bell 95dB
TEL605T-SE-HS50S-ip coiled cord – Bell 95dB